

Dräger Flame 2300

The Dräger Flame 2300 is an explosion proof combined UVIR flame detector used for the detection of hydrocarbon based fires. The detector provides flexibility with its numerous output modes, and advanced design features ensure reliability in the detection of fires whilst at the same time providing excellent immunity to potential false alarm sources.



ST-474-2004

Simple installation and commissioning

Installation is simple! The detector is easily installed with a stainless steel mounting bracket; this can be rotated to ensure optimum positioning of the detector in relation to the potential fire source. Angular markings allow the positioning angles of the detector to be recorded for future reference.

Detector flexibility

As well as a 4 to 20 mA output and 3 relays, an optional RS 485 output is also available, which can be multi-dropped to a central location. This provides a number of options for detector monitoring and the triggering of the necessary control action upon the detection of a fire.

Automatic and manual optics checks

Automatic checks of the detector electronics and optics ensure no fault goes undetected. Additionally the test can be triggered manually at anytime.

Isolated 4 to 20 mA as standard

Complete flexibility enables the detector to be operated from a separate power

supply (as a 4 wire device) or as a 3 wire device where there is no requirement for an isolated output.

Easily visible status LED

A tri-coloured LED which is visible at the front of the detector provides a simple status indication to personnel in close proximity to the detector. Green indicates normal operation; yellow indicates a fault and red indicates the presence of radiation.

False alarm immunity

The Dräger Flame 2300 provides the highest level of false alarm immunity. This is because the detector requires both IR and UV sensors to alarm before the detector will itself output an alarm condition and such action ensures that false alarms are all but non-existent.

Worldwide Approvals

The Dräger Flame 2300 can be used worldwide with the following approvals: ATEX, IECEx, FM and CSA.



ST-341-2004

Dräger Flame 2300:
Explosion proof combined UVIR flame detector for hydrocarbon based fires

TECHNICAL DATA

Type	Explosion proof UVIR flame detector for hydrocarbon based fires		
Spectral response	IR 4.2 to 4.7 micron, UV 0.185 to 0.26 micron		
Field of view	Horizontal 90°, vertical 90°		
Sensitivity	0.1 m ² gasoline fire at 18 metres, 1 sq. foot fire at 60 feet		
Response time t90	3.3 seconds, typical; configurable up to 30 seconds		
Signal output	Fault	0 mA	
	Optics/electronics check failure	2 mA	
	Normal operation	4 mA	
	IR presence	8 mA	
	UV presence	12 mA	
	Fire pre-warning	16 mA	
	Fire	20 mA (factory configurable for latching/non-latching alarm)	
	3 relays for fault, alarm and accessory, ratings 125 VAC, 0.5 A; 30 VDC, 2 A		
	optional RS 485		
	Supply voltage	18 to 32 VDC, current consumption 175 mA quiescent state at 24 VDC	
Ambient conditions	Temperature	- 40 to + 70 °C, - 40 to + 158 °F	
	Pressure	915 to 1055 hPa, 27.9 to 31.2 inch of Hg	
	Humidity	0 to 99 %RH, non condensing	
Enclosure	IP 66 / NEMA 4X		
Cable entry	M20, M25, 1/2" NPT or 3/4" NPT		
Size (L x D, approx.)	275 mm x 155 mm, 10.8" x 6.1"		
Weight (approx.)	3.5 kg, 7.7 lbs		
Approvals	ATEX	II 2G EEx d IIC T6/T5 ; - 50 ≤ Tamb ≤ + 60 / + 70 °C	
	IECEX	Ex d IIC T6/T5 ; - 50 ≤ Tamb ≤ + 60 / + 70 °C	
	FM/CSA	Class I, Groups A, B, C, D	
		Class I, Zone 1, Groups IIA, IIB & IIC	
	Ex d II C; T6/T5; - 40 ≤ Tamb ≤ + 60 / + 70°C		

ORDER INFORMATION

Dräger Flame 2300, Al housing, M20 entries	23 50 424
Dräger Flame 2300, Al housing, M25 entries	23 50 430
Dräger Flame 2300, Al housing, 1/2" NPT entries	23 50 436
Dräger Flame 2300, Al housing, 3/4" NPT entries	23 50 442
Dräger Flame 2300, SS housing, M20 entries	23 50 427
Dräger Flame 2300, SS housing, M25 entries	23 50 433
Dräger Flame 2300, SS housing, 1/2" NPT entries	23 50 439
Dräger Flame 2300, SS housing, 3/4" NPT entries	23 50 445



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)1245 600560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.